
Sunny Apex

35W Solar Module

High Efficiency Back-Contact

- Sunny Apex's HOP series solar modules ranged from 35Watt to 155Watt
- Aesthetically using clear surface back-contact cells
- © Cells with High conversion efficiency above 23%
- Anodized aluminum improving corrosion resistance
- Excellent performance under low light conditions





Electrical Specifications

Model Type	SA-H35
Peak Power (Pmax)	35W
Module Efficiency	16.50%
Maximum Power Voltage (Vmp)	17.5V
Maximum Power Current (Imp)	2.00A
Open Circuit Voltage (Voc)	21.3V
Short Circuit Current (Isc)	2.2A
Power Tolerance	-5% / + 10%
Maximum System Voltage	70V
Norminal Operating Cell Temp.	46 °C (+/-2)

Mechanical Specifications


Cell type	Back contact high eff. Mono
Number of cells	33 cells in series
Weight	2.68kg [5.91lbs]
Dimensions	510 x 415 x 35mm
	[20.09 x 16.35 x 1.38in]
Frame	$> 15 \mu m$ clear anodized aluminum
Junction Box	IP 65 waterproof
Cables	4.00mm ² , 500mm
Connectors	MC4 compatible


Temperature Coefficients

Power	-0.32%/ °C
Voltage	-1.8mV/ °C

Warranties & Certifiations

Warranties	2 years product warranty, 20 years limited power
	warranty of 80% of the mnimum specificed power rating
Certificates	CE





Unit: mm [inch]

Note: All electrical parameters are rated at standard test conditions (irradiance of 1000W/m², AM 1.5G, cell temperature 77°F/25°C)

Caution: Read Safety and Installation Instruction before using this product.

2017 Sunny Apex Development Ltd. All right reserved. Specifications included in this datasheet are subject to change without notice.

Sunny Apex Development Limited

www.sunnyapex.com